

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Орenburg (3532)37-68-04
Пенза (8412)22-31-16
Казахстан (772)734-952-51

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<https://telwin.nt-rt.ru/> || tnw@nt-rt.ru

STARTZILLA 9024 XT 12V/24V



XT NEW

Overview

STARTZILLA 9024 XT 12V/24V

cod. 829525

Multifunction electronic starter, power supply and tester, with LiFePO4 lithium battery for 12V/24V starting of cars, vans, small boats, lorries etc.

It performs control tests on the battery: voltage at terminals, starting capacity (CCA) and operational check of the vehicle alternator.

The OVER RIDE function allows starting in emergency conditions when battery is missing (or completely down).

It is a stable and reliable power supply source for battery changes (SUPPLY function).

Robust and compact, it is equipped with high intensity LED light.

Protection against: polarity reversal, short-circuit, overvoltage (incompatible battery voltage), undervoltage (cut-off voltage), overcurrent, overheating, under-temperature, accidental contacts, alternator return currents.

Complete with starting cables and wall charge.



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 829525	START	STARTING VOLTAGE 12 / 24 V	DIMENSIONS	15,5 x 23,4 x 31,8 cm
MAINS VOLTAGE	100 - 240 V	MAX STARTING CURRENT	9000 A	WEIGHT	4,33 kg
PROTECTION DEGREE	IP43	EAN CODE	8056151814623	CAPACITY	31200 mAh